

REFERENCES

- [1] Kleyne, E.G. (1975). *The Use of Dynamic Cone Penetrometer (DCP): 2/74*, Transvaal Roads Department, Pretoria.
- [2] Karunaprema, K.A.K., & Edirisinghe, A.G.H.J., (2001). *Dynamic Cone Penetrometer and its use in Highway Engineering*. Transactions: Institution of Engineers Sri Lanka, pp. 56-65.
- [3] Smith, R.B., & Pratt, D.N., (1983). *A Field Study of in Situ California Bearing Ratio and Dynamic Cone Penetrometer Testing for Road Subgrade Investigations*. Australian Road Research, Vol.13, No.4, pp. 285-294.
- [4] Liveneh, M., & Ishia, I., (1987). Pavement and Material Evaluation by a Dynamic Cone Penetrometer. *Sixth international Conference on the Structural Design of Asphalt Pavement*, Vol.1, Ann Arbor, Michigan, pp. 665-674.
- [5] O'Flaherty, C.A., (1967). *Highway Engineering Vol .2* .London: Edward Arnold
- [6] Road Development Authorities. Official Web Site Retrieved March, 2012, www.rda.gov.lk
- [7] Taneja, & Ashima Singh. (February 2012). International Journal of Research in Engineering & Applied Sciences. Retrieved, March 30, 2012, from <http://www.euroasiapub.org>.
- [8] Parampreet Kaur, K. S., Gill, B. S., Walia, (2012). Correlation between soaked CBR value and CBR value obtained with Dynamic Cone Penetrometer (DCP) test. *International Journal in Research engineering & Applied Sciences*. Retrieved March 30, 2012, from <http://www.euroasiapub.org>
- [9] Karunaprema, K.A.K., & Edirisinghe, A.G.H.J., (2003). *A Laboratory Investigation on the Relationship between Dynamic Cone Penetrometer value and Soaked California Bearing Ratio*. Transactions: Institution of Engineers Sri Lanka, pp. 120-122.
- [10] Mukesh, A. P., & Dr. Patel, H.S., (2012). *Correlation between Physical Properties and California Bearing Ratio Test on Soils of Gujarat Region in*

Both in Soak and Unsoak Condition. Retrieved April 30, 2013, from
1map_technical@yahoo.co.in, 2dr.hspatel@yahoo.com



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk