

## REFERENCES

- \* Das. B.M., - Advanced Soil Mechanics, 1985.  
McGraw – Hill International Edition
- \* Kulathilaka S.A.S (1999) –“Improvement of peat by preconsolidation”. Proceedings of the Eleventh Asian Regional Conference on Soil Mechanics and Geotechnical Engineering in Seoul, South Korea. Pp97-100
- \* S.K Lee, Weels White and Owen G Sngles –Geotechnical Engineering Pitman Publication. 1983
- \* Wojciech Wolsk, Alijzy Szymanski, “Two Stage- Construced Embankment on Organic Soils”, Swedish Geotachnical Engineering Report- No 32.
- \* Yuan Chun Eugene Chang, “Long Term Consolidation beneath the Test Fills at Vasby, Sweden” , Swedish Geotachnical Engineering Report- No 13.
- \* Mesri G., Stark T.D., Ajlouni M.A., Chen C.S., “Secondary Compression of Peat with or without Surcharging”, Journal of Geotechnical and Geoenvironmental Engineering Volume No. 5, May 1997
- \* Hobbs N.B., (1986), “ Mire morphology and the properties and behavior of some British and Foreign Peats quarterly”, Journal of Engineering Geology, 19 Vol. 1,7-80.
- \* Munasinghe W.G.S. (2001)- “Improvement of Engineering Properties of Peat – A Comparative Study”, M.Eng. Thisis, Department of Civil Engineering, University of Moratuwa.
- \* Perera A.G.S, Karunawardena W.A., Botejue W.D.R. (1998)- “Improvement of Peat by Preloading method” .Final Year Undergraduate Project, Department of Civil Engineering, University of Moratuwa.

