

TCP PERFORMANCE EVALUATION IN A VSAT LINK

This dissertation was submitted to the Department of Electronic &

Telecommunication Engineering, University of Moratuwa in partial fulfillment of the
requirements for the Degree of M.Sc. in Telecommunications

Department of Electronic & Telecommunication Engineering
University of Moratuwa

Supervisor
MR. KITHSIRI SAMARASINGHE

K.M. FERNANDO

2009

93921

Abstract

The Transmission Control Protocol (TCP) is the mostly used protocol for data transmission over networks. However, TCP's congestion control algorithm wasn't created to match the special characteristics of satellite links, resulting in a drastically performance degradation. TCP appears in different algorithm versions, all with different features but with maximal throughput as their main objective. The aim of this paper is to evaluate and compare six TCP versions, which are Tahoe, Reno, New Reno, Sack, Fack, and Vegas, when applied over GEO satellite VSAT links in TCP connections, using Ns-2 simulation. Suitable scenarios based on a GEO bent-pipe satellite have been implemented. I evaluate the performance of the above mentioned TCP versions over GEO VSAT-based satellite links and compare it with the performance of a real VSAT link. It was found that the flow and congestion control mechanism used in some of TCP versions were unable to reach full utilization on VSAT link speeds.

Keywords: Transmission Control Protocol (TCP), Very Small Aperture Terminals (VSAT), TCP Tahoe, TCP Reno, TCP Sack, TCP New Reno, TCP Sack, TCP Vegas, TCP Fack.

DECLARATION

I certify that this dissertation does not incorporate without acknowledgement any material previously submitted for a degree in any University to the best of my knowledge and believe that it does not contain any material previously published. written or orally communicated by another person or myself except where due reference is made in the text. I also hereby give consent for my dissertation, if accepted, to be made available for photocopying and for inter-library loans, and for the title and summary to be made available to outside organizations.

UOM Verified Signature

Signature of the Candidate

Electronic Theses & Dissertations www.lib.mrt.ac.lk

To the best of my knowledge, the above particulars are correct.

UOM Verified Signature

Supervisor

A T L K Samarasinghe

Department of Electronic & Telecommunication Engineering University of Moratuwa, Sri Lanka

ACKNOWLEDGEMENTS

First and foremost I would like to thank Mr.Kithsiri Samarasinghe (Head of the Department, Electronics and Telecommunication) for all his support and enthusiasm toward the "TCP Performance Evaluation in a Vsat Link" research topic. He provided a graet deal of encouragement and guidance by providing information related to satellite communications.

Also I would like thank Dr. Ajith Pasqual (Senior Lecturer Department of Electronics and Telecommunication) for all his excellence coordination of the MSc research program.

Next I extend my gratitude to all of my friends, for their support and encouragement extended towards the successful completion of this research project. Finally, I would like to thank my family for their constant love and unending support.



TABLE OF CONTENTS

DE	CLARA	IONi	
ΑB	STRAC	iii	
AC	KNOWI	EDGMENTSiv	
TΑ	BLE OF	CONTENTv	
LIS	ST OF E	GURESvii	
LIS	ST OF T.	BLESix	
1.	INTD (DUCTION 1	
1.	1.1	DUCTION 1 Motivation of TCP 1	
	1.1	Issues	
	1.3	Scope of works	
	1.4	Evolution of TCP	
	1.5	Satellite communication	
		1.5.1 Time Delay	
		1.5.2 Sun Interference	
		1.5.3 Uscintillation of Moratuwa, Sri Lanka. 12	
		1.5.4 Satellite Applications Dissertations 12	
		1.5.4.1 Digital voice communication	
		1.5.4.2 Broadband IP services	
		1.5.4.3 Broadcasting services	
		1.5.4.4 VSAT services	
2.	LITER	ATURE REVIEW 16	
	2.1	TCP	
		2.1.1 TCP Logical Connection	
	2.2 TCP Versions.		
		2.2.1 Older Versions	
		2.2.1.1 TCP Tahoe	
		2.2.1.2 TCP Reno. 20	
		2.2.1.3 TCP Newreno	

			2.2.1.4	TCP Vegas	23			
			2.2.1.5	TCP SACK	25			
			2.2.1.6	TCP Westwood	26			
		2.2.2	TCP for	High Bandwidth-Delay Product Networks	28			
			2.2.2.1	Highspeed TCP	28			
			2.2.2.2	Scalable TCP	28			
	2.3	VSAT	Commun	ication	31			
		2.3.1	VSAT N	etwork Applications	32			
		2.3.2	Radio Fr	requency Characteristics of VSAT Networks	33			
		2.3.3	Access T	echniques	33			
			2.3.3.1	Random Access	34			
			2.3.3.2	Demand assigned Multiple Access	36			
			2.3.3.3	Fixed-Assigned FDMA	36			
		2.3.4	Outboun	d TDM Channel	37			
3,	METH	ODOLO	OGY		39			
	3.1	Overvi	ew of NS-	2 simulation	39			
	3.2							
	3.3			witemTheses & Dissertations	43			
4.	SIMUL	ATION	RESUL	TS	45			
	4.1 Tahoc, Reno, NewReno, Sack, Fack and Vegas Results							
	in a Simulated VSAT Link							
	4.2 Performance over varying parameters							
	4.2.1 Varying TCP Window Size5							
	4.2.2 Varying Bit Error Rate							
		4.2.3	Varying th	ne File Size	56			
	4.3 R	teal New	work Perfo	ormance	57			
5.	CONC	LUSIO	N		59			
	5.1	Major	results		59			
	5.2	Future	e works		60			
В	IBLIOG	RAPHI	CAL REI	FERENCES	61			

LIST OF FIGURES

Figure 1.1: Illustration of TCP congestion window behaviors
Figure 1.2: Orbit Types for Satellites
Figure 1.3: Sky noise and frequency bands
Figure 1.4: Cases of sun interference
Figure 1.5: VSAT System
Figure 2.1:TCP Segment format
Figure 2.2: Scalable TCP Congestion Window Properties [60]
Figure 2.3: The conventional VSAT star network configuration
Figure 2.4: A VSAT network based on mesh architecture
Figure 2.5: Reservation mode transmission
Figure 2.6: Throughput versus delay performance of some Aloha schemes
(From ITU-R Supplement 3
to Handbook of Satellite Communications
Figure 2.7: The HDLC frame format
Figure 3.1: Illustration of The duality of C++ and OTel in sharing class hierarchy40
Figure 3.2: Illustration of Simplified User's View of NS-2
Figure 3.3 Network Diagram of the Simulation Set-up
Figure 3.4 NAM Window of NS-2 Network Simulator
Figure 3.5 Physical Test-bed
Figure 4.1: Throughput of Tahoe, Reno, New Reno, Sack, Fack and Vegas TCP
variants over a 384Kbps VSAT Link
Figure 4.2: Output buffer size of R1 router in R1 – R2 Link for Tahoe, Reno,
New Reno, Sack, Fack and Vegas TCP variants over a 384Kbps
VSAT Link47
Figure 4.3 Packet Sequence No received by the TCP receiver with the Time
Figure 4.4 Congestion window of TCP sender Vs time for Tahoe, Rono,
New Reno, Sack, Fack and Vegas TCP variants over
a 384Kbps VSAT Link49
Figure 4.5: Slow Start Threshold value variation with the Time for Tahoe,
Reno New Reno Sack Fack and Vegas TCP variants over

a 384Kbps VSAT Link5	i()
Figure 4.6 :Throughput of Tahoe, Reno, New Reno, Sack, Fack and	
Vegas TCP variants over a 384Kbps VSAT Link with 8KB	
Window Size.	51
Figure 4.7: Throughput of Tahoe, Reno, New Reno, Sack, Fack and	
Vegas TCP variants over a 384Kbps VSAT Link with	
17KB Window Size	52
Figure 4.8: Throughput of New Reno and Vegas TCP variants over	
a 384Kbps VSAT Link with varying Window Size	53
Figure 4.9: Packet Sequence No received by the TCP receiver with	
the Time at 10-7 BER	54
Figure 4.10 (Packet Sequence No received by the TCP receiver with	
the Time at 10-5 BER for Tahoe, Reno, New Reno, Sack,	
Fack and Vegas TCP variants.	55
Figure 4.11: Packet Sequence No of Vegas at 10-5, 10-6, and 10-7 BER values5	55
Figure 4.12 :Packet Sequence No with different file sizes.	56
Figure 4.13 :Throughput of Tahoe. Reno, New Reno, Sack, Fack and	
Vegas TCP variants over a 384Kbps VSAT Link with	
different file sizes. Theses & Dissertations	7
Figure 4.14: Throughput of Windows XP FTP server-client over a 384Kbps	
VSAT Link with a 2Mbyte file transfer.	57
Figure 4.15 :Packet Sequence No with time	58

LIST OF TABLES

Table 2.1: Random Access Schemas comparison	34
Table 2.2: Comparison of Multiple Access Techniques	.37
Table 3.1: Parameters set used in VSAT Link Simulation.	.43
Table 3.2: Illustration of PER corresponding to BER.	.42
Table 4.1: Parameters set used in VSAT Link Simulation.	45
Table 4.2 Average Throughput with different file sizes	56

