



**COMPARISON AND PERFORMANCE EVALUATION
OF SUBMERGED ATTACHED GROWTH AEROBIC
SYSTEM VERSUS SUSPENDED GROWTH AEROBIC
SYSTEM
DESIGNED FOR FACTORY SEWAGE**

THIS DISSERTATION IS SUBMITTED TO THE DEPARTMENT OF
CIVIL ENGINEERING PARTIAL FULFILLMENT OF THE
REQUIREMENTS FOR THE DEGREE OF MASTER IN
ENVIRONMENTAL MANAGEMENT

by

LA.S.L. Athukorala

Supervised by

Dr. Mahesh Jayaweera

Dr. Jagath Manatunge

Department of Civil Engineering

University of Moratuwa

Sri Lanka

2010

94857



Abstract

Most factories found in Sri Lanka do not have proper sewage treatment systems and due to the high number of employees these factories are always encountered with the problem of handling large quantities of low strength sewage generated from lavatories, canteens and kitchens. In such factories sewage is usually handled using conventional septic tank - soakage pit systems. Such systems are commonly found infested with insects, and promote further breeding. They cause nuisance due to obnoxious odor, and is a major cause for severe ground and surface water pollution. It has been noted that these factories have critical problems of handling sewage during rainy season, especially when the factory is located in areas with high ground water table such as a marshy land or near a surface water body.

However, some factories consist of a conventional activated sludge system and a higher percentage of activated sludge processes found in these factories are in the malfunctional stage due to the least attention by the factory management. The activated sludge systems require a very high attention for the proper operation.

The major problem of such factories is the giving of the least priority for the above issue and therefore the allocation of competent personal to operate plant is neglected. ,.' Therefore, their key demand is to provide them a treatment system to treat sewage with minimal operational difficulties and minimal labour involvement to overcome above problem.

This research was therefore carried out with the following objectives to fulfill the above requirement. The broad objective is the study and compare the performance of aerobic attached growth and aerobic. suspended growth processes designed for factory sewage and recommend the most appropriate treatment regime for the factory sewage with regard to less operational and maintenance issues.

Therefore, BOD removal efficiency and nitrogen removal efficiency have been compared for both processes in order to evaluate the performance of the each



process. The estimation of sludge wasting, appropriation of process control parameters and operational issues in both processes are studied for the justification of the operational feasibility of each process. The land utilization and operational and maintenance cost have been estimated to identify the economical feasibility of each process.

This study has proved that the BOD removal efficiencies of each process are equal and the nitrogen removal percentages are 43 % and 37% in attached growth process and suspended growth process respectively.


Sludge production is 27 % less in attached growth process and thereby sludge handling is easy and esthetically good. The operational issues have been proved less in attached growth process.

Annual operational and maintenance cost for the attached growth aerobic process is 30 % less over suspended growth aerobic process. Land requirement (foot print) is 13 % less in attached growth process over suspended growth process. Unit cost *Rs*/m³ of treated water for attached growth process has been proved that 32% less.

Therefore, submerged attached growth system is, recommended as a less complicated, trouble free method for treatment of the factory sewage.

DECLARATION

I declare that this thesis does not incorporate without acknowledgement any material previously submitted for a Degree or Diploma in any University or other institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where the acknowledgement is made in the text.



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

S. I. Athukorala

DECLARATION

I have supervised and accepted this thesis for the submission of the Degree

Certified by:

UOM Verified Signature

.

Dr. Mahesh Jayaweera

Project Supervisor

Department of Civil Engineering

University of Moratuwa

Sri Lanka

Λ

UOM Verified Signature

/

Dr. Jagath Manatunge

Project Supervisor

Department of Civil Engineering

University of Moratuwa

Sri Lanka



TABLE OF CONTENTS

Declaration of the candidate	I
Declaration of the supervisor	II
Acknowledgements	III
Abbreviations	IV
Table of contents	VI
Notes	XI
Figures	XIII
Abbreviations	XIV
1 Introduction	1
1.1 Domestic wastewater treatment	1
1.1.1 Suspended growth process	2
1.1.2 Submerged attached growth process	3
1.2 Present scenario in treatment of sewage in factories	4
1.3 Problem identification: a case study	5
1.4 Objectives and the Scope of the Research	6
2 Theoretical considerations and literature review	7
2.1 Strength of sewage effluent	7
2.2 Domestic wastewater treatment	7
2.2.1 Suspended growth process	8
2.2.1.1 Process control in activated sludge process	8

2.2.1.2	Problems in activated sludge process	9
2.2.1.2.1	Sludge bulking	9
2.2.1.2.2	Rinsing of sludge	9
2.2.1.2.3	Nocardia foaming	10
2.2.2	Attached growth aerobic process	10
2.2.2.1	Nonsubmerged attached growth process	11
2.2.2.2	Suspended growth process with fixed – film packing	11
2.2.2.3	Submerged attached growth process	11
2.2.2.3.1	Substrate removal mechanism in submerged attached growth process	12
2.2.2.3.2	Advantages of submerged attached growth aerobic systems over activated sludge process	13
2.2.3	Biological Nitrogen Removal	14
2.2.3.1	Biological nitrification	14
2.2.3.1.2	Process description of nitrification	14
2.2.3.1.3	Microbiology in nitrification	15
2.2.3.1.4	Stoichiometry of Biological Nitrification	15
2.2.3.2	Biological denitrification	16
2.2.3.2.1	Process description of denitrification	16
2.2.3.2.2	Microbiology in denitrification	17
2.2.3.2.3	Stoichiometry of Biological Denitrification	17

Chapter 3: Materials and methods	18
3.1 Study area	18
3.2 Methodology	21
3.2.1 Start up	21
3.2.2 Operation of the trial	21
3.2.3 Sampling points and corresponding chemical analysis of attached growth aerobic process	22
3.2.4 Sampling points and corresponding other analysis of attached growth aerobic process	22
3.2.5 Sampling points and corresponding chemical analysis of suspended growth aerobic process	23
3.2.6 Sampling points and corresponding other analysis of suspended growth aerobic process	23
3.2.7 Experimental techniques	24
3.2.8 Chemical analysis	25
Chapter 4 : Results and discussion	26
4.1 Estimation and Verification of Flow Rate	26
4.2 Influent Parameters (COD, BOD, pH, TSS)	28
4.3 Manipulation of Process Control Parameters	34
4.3.1 Dissolved oxygen	35
4.3.2 MLVSS	38
4.3.3 F/M ratio	40



4.3.4	SVI	40
4.4	Characteristics of Treated Water (COD, BOD, pH, TSS)	42
4.5	BOD Removal Efficiency	48
4.6	Nitrogen Removal Efficiency	48
4.7	Sludge Wasting	52
4.7.1	Sludge wasting in attached growth process	52
4.7.2	Sludge wasting in suspended growth process	54
4.8	Plant Foot Print	55
4.8.1	Design of an anaerobic sludge digester	56
4.8.1.1	Design of an anaerobic sludge digester for attached growth aerobic process	56
4.8.1.2	Design of an anaerobic sludge digester for suspended growth aerobic process	57
4.8.2	Design of sludge drying beds	57
4.8.2.1	Design of sludge drying beds for attached growth Aerobic process	57
4.8.2.2	Design of sludge drying beds for suspended growth aerobic process	58
4.8.3	Foot print calculation for each process	58
4.8.3.1	Foot print calculation for attached growth aerobic process	58
4.8.3.2	Foot print calculation for suspended growth aerobic process	59

4.9	Operational issues	59
4.9.1	Sludge bulking	60
4.9.2	Sludge handling	61
4.9.3	Rinsing of sludge	61
4.9.4	Nocardia foaming	61
4.10	Cost Calculation	62
4.10.1	Capital cost	62
4.10.1.1	Capital cost for attached growth aerobic process	62
4.10.1.2	Capital cost for suspended growth aerobic process	64
4.10.2	Annual operational cost	65
4.10.2.1	Attached growth process	65
	4.10.2.1.1 Energy cost	65
	4.10.2.1.2 Cost of operating staff	66
4.10.2.2	Suspended growth aerobic system	67
	4.10.2.2.1 Energy cost	67
	4.10.2.2.2 Cost of operating staff	67
4.10.3	Unit cost calculation	69
4.11	Comparison of two treatment processes	72
Chapter 5	: Conclusions and recommendations	73
5.1	Conclusions	73
5.2	Recommendations	73
5.3	Further studies recommended	73

LIST OF TABLES

Table 3.1:	Sampling points and corresponding chemical analysis – attached growth process	22
Table 3.2:	Sampling points and corresponding chemical analysis – suspended growth process	23
Table 3.3:	Sampling points and other analysis – suspended growth process	24
Table 4.1:	Estimation of the wastewater flow rate – attached growth process	26
Table 4.2:	Estimation of the wastewater flow rate – suspended growth process	27
Table 4.3:	Daily variation of influent characteristic in the equalization tank	29
Table 4.4:	Influent characteristic – attached growth process	30
Table 4.5:	Influent characteristic – suspended growth process	31
Table 4.6:	DO concentrations – attached growth process	36
Table 4.7:	DO concentrations – Suspended growth process	37
Table 4.8:	MLVSS and F/M values	38
Table 4.9:	SVI in the aeration tank	41
Table 4.10:	Analysis summary – attached growth process	43

LIST OF FIGURES

Figure 1.1:	Suspended growth process	1
Figure 1.2:	Attached growth process	1
Figure 1.3:	Schematic diagram of activated sludge process	2
Figure 1.4:	Attached growth process description	3
Figure 2.1:	Schematic representation of the cross section of a biological slime layer	12
Figure 3.1:	Selected treatment plant for the trial	19
Figure 3.2:	PFD	20
Figure 4.1:	BOD variation- influent	32
Figure 4.2:	COD variation- influent	32
Figure 4.3:	TSS variation- influent	33
Figure 4.4:	pH variation- influent	33
Figure 4.5:	BOD variation- effluent	45
Figure 4.6:	COD variation- effluent	45
Figure 4.7:	TSS variation- effluent	46
Figure 4.8:	pH variation- effluent	46
Figure 4.9:	BOD removal efficiency	47

LIST OF ABBREVIATIONS

BOD	– Bio-chemical Oxygen Demand
CEA	– Central Environmental Authority
COD	– Chemical Oxygen Demand
DO	– Dissolved Oxygen
MSS	– Mixed Liquor Suspended Solids
MVSS	– Mixed Liquor Volatile Suspended Solids
RBC	– Rotating Biological Reactor
SRT	– Solids Retention Time
TSS	– Total Suspended Solids
STP	– Sewage Treatment Plant
TKN	– Total Kjeldahl Nitrogen
VSS	– Volatile Suspended Solids
SVI	– Sludge Volume Index
SRR	– Sludge Return Rate
SVI	– Stirred Sludge Volume Index



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

APPENDIXES

Appendix A:	Statistical data analysis of means of influent flow rate	75
Appendix B:	Statistical data analysis of BOD variation	77
Appendix C:	Statistical data analysis of COD variation	79
Appendix D:	Statistical data analysis of TSS variation	81
Appendix E:	Biological calculation for suspended growth process at SRT- 4 days	83
Appendix F:	Biological calculation for suspended growth process at SRT- 10 days	86



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

