

REFERENCES

- [1] R. Hyde, *Climate Responsive Design: A Study of Buildings in Moderate and Hot Humid Climates*. 2000.
- [2] V. Olgyay, *Design with Climate: Bioclimatic Approach to Architectural Regionalism*. Elsevier Ltd, 1963. doi: 10.1016/j.jenvman.2014.05.006.
- [3] B. Givoni, *Man, climate, and architecture*, vol. 6, no. 8. 1969. [Online]. Available: https://www.researchgate.net/profile/Kovo_Akpomie/publication/312611250_Effect_of_cassava_peel_on_the_insulating_properties_of_ogugu_clay_deposit/links/59613084a6fdccc9b114927a/Effect-of-cassava-peel-on-the-insulating-properties-of-ogugu-clay-deposit.pdf
- [4] M. Rajapaksha, U. Rajapaksha, and I.-K. Rajapaksha, “Passive climate modification in compact house forms in Galle fort, A case of thermal mass integration,” 2013.
- [5] N. Jamaludin, M. Faris Khamidi, S. Ngah, A. Wahab, and M. M. A. Klufallah, “Indoor Thermal Environment in Tropical Climate Residential Building”, doi: 10.1051/C.
- [6] O. K. Akande and M. A. Adebamowo, “Indoor Thermal Comfort for Residential Buildings in Hot-Dry Climate of Nigeria.” [Online]. Available: <http://nceub.org.uk>
- [7] N. Jamaludin, M. Faris Khamidi, S. Ngah, A. Wahab, and M. M. A. Klufallah, “Indoor Thermal Environment in Tropical Climate Residential Building”, doi: 10.1051/C.
- [8] B. C. M. Rodriguez and M. D. Alessandro, “Indoor thermal comfort in the tropics,” no. October, 2019.
- [9] Baruch.Givoni, E. M. González-cruz, E. Gonzalez, and U. Zulia, “Thermal Performance of Indirect Evaporative Cooling in a Tropical Climate thermal performance of indirect evaporative cooling in a tropical,” no. May 2009, 2009, doi: 10.13140/RG.2.1.3813.4486.
- [10] B. Givoni and E. Gonzalez, “Thermal performance of indirect evaporative cooling in a tropical climate,” *38th ASES National Solar Conference 2009, SOLAR 2009*, vol. 3, no. May 2009, pp. 1734–1769, 2009, doi: 10.13140/RG.2.1.3813.4486.
- [11] N. V. Baker, *Passive and low energy building design for tropical island climates*, vol. 35, no. 4. 1987.

- [12] P. O. Akadiri, E. A. Chinyio, and P. O. Olomolaiye, "Design of a sustainable building: A conceptual framework for implementing sustainability in the building sector," *Buildings*, vol. 2, no. 2, pp. 126–152, 2012, doi: 10.3390/buildings2020126.
- [13] B. Givoni, *Man, Climate and Architecture*, no. October 2012. 1976. doi: 10.4236/jmmce.2012.1110097.
- [14] A. Dimoudi, "Passive cooling of buildings," *Passive Cooling of Buildings*, no. January 2005, pp. 35–55, 2013, doi: 10.4324/9781315073668.
- [15] A. Ragheb, H. El-Shimy, and G. Ragheb, "Green Architecture: A Concept of Sustainability," *Procedia - Social and Behavioral Sciences*, vol. 216, pp. 778–787, Jan. 2016, doi: 10.1016/j.sbspro.2015.12.075.
- [16] D. Asimakopoulos and M. Santamouris, *Passive Cooling of Buildings*, no. August 2016. 1996.
- [17] S. J. Emmerich, "Simulated performance of natural and hybrid ventilation systems in an office building," *HVAC and R Research*, vol. 12, no. 4, pp. 975–1004, 2006, doi: 10.1080/10789669.2006.10391447.
- [18] S. Omrani, V. Garcia-Hansen, B. Capra, and R. Drogemuller, "Effect of natural ventilation mode on thermal comfort and ventilation performance: Full-scale measurement," *Energy and Buildings*, vol. 156, no. 4, pp. 340–351, 2017, doi: 10.1520/gtj10248j.
- [19] O. Amer, R. Boukhanouf, and H. G. Ibrahim, "A Review of Evaporative Cooling Technologies," *International Journal of Environmental Science and Development*, vol. 6, no. 2, pp. 111–117, 2015, doi: 10.7763/IJESD. 2015.V6.571.
- [20] L. S. DimoudiA, Androutopoulos A, "Experimental work on a linked, dynamic and ventilated, wall component.," *Energy and Buildings*, vol. 122, pp. 386–396, 2004, doi: 10.1016/j.buildenv.2017.06.026.
- [21] EBC Annex 62, "Ventilative cooling," *EBC Annex 62*. pp. 1–5, 2018.
- [22] G. Gan, "Interaction Between Wind and Buoyancy Effects in Natural Ventilation of Buildings," *The Open Construction and Building Technology Journal*, vol. 4, no. 1, pp. 134–145, Dec. 2010, doi: 10.2174/1874836801004010134.
- [23] R. Barbosa, M. Barták, J. L. M. Hensen, and M. G. L. C. Loomans, "Ventilative cooling control strategies applied to passive house in order to avoid indoor overheating," *14th*

International Conference of IBPSA - Building Simulation 2015, BS 2015, Conference Proceedings, no. 2015, pp. 1142–1148, 2015.

- [24] R. Hyde *et al.*, “Design Solution Sets for Bioclimatic Retrofit,” *Sustainable Retrofitting of Commercial Buildings*, no. February, pp. 61–88, 2019, doi: 10.4324/9780203119846-7.
- [25] T. Standard and I. Ministry, “Engineering Standard for Process Design of Fans and Blowers Original Edition,” 1998.
- [26] S. S. Cunha I, Strack T, ““Fans and Blowers ; Energy efficiency reference guide’, CEATI International Inc.,” *Building and Environment*, vol. 139, no. May, pp. 134–145, 2008, doi: 10.1016/j.buildenv.2018.05.025.
- [27] A. G. Kwok, “Thermal Comfort in Naturally-Ventilated and Air-Conditioned Classrooms in the Tropics,” 1990. [Online]. Available: <https://escholarship.org/uc/item/65d3k1jt>
- [28] A. G. Kwok, “Thermal Comfort in Naturally-Ventilated and Air-Conditioned Classrooms in the Tropics,” 1990. [Online]. Available: <https://escholarship.org/uc/item/65d3k1jt>
- [29] J. F. Straube and E. F. P. Burnett, “Vents, Ventilation and Masonry Veneer Wall Systems,” *In Proceedings of the Eighth Canadian Masonry Symposium. Jasper, Alta., Canada*, no. December, p. (pp.-194-207), 1998, [Online]. Available: https://www.researchgate.net/publication/237552112_Vents_ventilation_and_masonry_veneer_wall_systems
- [30] S. Boddy and J. Krigger, “Cooling Your Home with Fans and Ventilation.”
- [31] B. Givoni, *Passive and Low Energy Cooling of Buildings*, vol. 34, no. 1. 1994. doi: 10.17221/1846-hortsci.
- [32] B. Givoni, “Comfort, climate analysis and building design guidelines,” *Energy and Buildings*, vol. 18, no. 1, pp. 11–23, 1992, doi: 10.1016/0378-7788(92)90047-K.
- [33] Amos Rapoport, *House form and culture*. 1969.
- [34] S. V. Szokolay, *Introduction to Architectural Science: The Basis of Sustainable Design*, vol. 11, no. 2. 2012. doi: 10.3130/jaabe.11.407.
- [35] O. H Koenigsberger, *Manual of tropical housing building*, vol. 7, no. November. 1973. doi: 10.3126/jsce.v7i0.26786.

- [36] “Green building materials-a Way towards Sustainable Construction Editor IJAIEM International Journal of Application or Innovation in Engineering & Management (IJAIEM) Web Site: www.ijaiem.org Email: editor@ijaiem.org Volume 4, Issue 4,” 2015. [Online]. Available: www.ijaiem.org
- [37] B. Venkatarama Reddy, “Sustainable materials for low carbon buildings,” *International Journal of Low-Carbon Technologies*, vol. 4, no. 3, pp. 175–181, Jul. 2009, doi: 10.1093/ijlct/ctp025.
- [38] G. H. Galabada, M. Rajapaksha, F. R. Arooz, and R. Halwatura, “Identifying the Impact of Concrete Specimens Size and Shape on Compressive Strength A Case Study of Mud Concrete,” 2019. [Online]. Available: www.etasr.com
- [39] T. A. G. L. J. Glover, D. O. White, “Wood versus Concrete and Steel in House Construction: A Life Cycle Assessment,” *Building and Environment*, vol. 100, pp. 104–114, doi: 10.1016/j.buildenv.2016.10.003.
- [40] J. C. Morel, A. Mesbah, M. Oggero, and P. Walker, “Building houses with local materials: means to drastically reduce the environmental impact of construction,” *Building and Environment*, vol. 36, no. 5, pp. 2141–2149, 2001, doi: 10.1016/j.buildenv.2006.04.005.
- [41] B. H. Rojero, J. N. S. Cuizon, R. L. Menchavez, and S. A. Nawang, “Porous Red Clay-Based Ceramics Fabricated by Pore Self-Forming Technique Porous Red Clay-Based Ceramics Fabricated by Pore Self-Forming Technique,” no. December 2018, 2019.
- [42] P. B. Lourenço, F. M. Fernandes, and F. Castro, “Handmade clay bricks: Chemical, physical and mechanical properties,” *International Journal of Architectural Heritage*, vol. 4, no. 1. Routledge, pp. 38–58, 2010. doi: 10.1080/15583050902871092.
- [43] G. E. Christidis, “Industrial clays,” *European Mineralogical Union Notes in Mineralogy*, vol. 9, no. 1, pp. 341–414, 2011, doi: 10.1180/EMU-notes.9.9.
- [44] M. la Noce, A. lo Faro, and G. Sciuto, “Clay-Based Products Sustainable Development: Some Applications,” 2021, doi: 10.3390/su13031364.
- [45] G. Reboux, A. P. Bellanger, S. Roussel, F. Grenouillet, and L. Millon, “Moulds in dwellings: Health risks and involved species,” *material and environment*, vol. 42, no. 10, pp. 3540–3546, 2011, doi: 10.1016/j.buildenv.2006.10.016.

- [46] A. Bouchair, ““Terra Literature Review: An Overview of Research in Earthen Architecture Conservation,”” *Building and Environment*, vol. 43, no. 10, p. 174., 2008, doi: 10.1016/j.buildenv.2007.10.005.
- [47] P. J. Khedari, Watsanasathaporn, and J. Hirunlabh, ““Development of fibre-based soil–cement block with low thermal conductivity,”” *Building and Environment*, vol. 38, no. 1, pp. 185–193, 2004, doi: 10.1016/S0360-1323(02)00012-4.
- [48] M. C. Jiménez Delgado and I. C. Guerrero, ““The selection of soils for unstabilised earth building: A normative review,”” *Construction and Building Materials*, vol. 40, no. 12, pp. 1591–1601, 2007, doi: 10.1016/j.buildenv.2004.12.004.
- [49] A. A. Raheem, O. A. Bello, and O. A. Makinde, ““A comparative study of cement and lime stabilized lateritic interlocking blocks,”” *Building and Environment*, vol. 11, no. 1, pp. 25–54, 2010, doi: 10.1016/j.buildenv.2005.07.030.
- [50] F. Pacheco-Torgal and S. Jalali, ““Earth construction: Lessons from the past for future eco-efficient construction,”” *Construction and Building Materials*, vol. 44, no. 2, pp. 431–436, 2012, doi: 10.1016/j.buildenv.2008.02.011.
- [51] B. Berge, “The Ecology of Building Materials.,” *Building and Environment*, vol. 44, no. 4, pp. 826–838, 2009, doi: 10.1016/j.buildenv.2008.05.020.
- [52] S. Deboucha and R. Hashim, ““A review on bricks and stabilized compressed earth blocks,”” *Building and Environment*, vol. 42, no. 2, pp. 926–932, 2011, doi: 10.1016/j.buildenv.2005.10.017.
- [53] A. Ramos, M. P. Sáez, M. A. Rodríguez, M. N. Antón, J. Gómez, and P. Piloto, “Thermal properties of fired clay bricks from waste recycling. A review of studies,” *Fire Research*, vol. 3, no. 1, Oct. 2019, doi: 10.4081/fire.2019.71.
- [54] K. A. Heathcote, ““Durability of earthwall buildings,”” *Construction and Building Materials*, vol. 45, no. 6, pp. 1422–1433, 1995, doi: 10.1016/j.buildenv.2009.12.005.
- [55] J. Folaranmi, “Effect of Sawdust Additive on the Properties of Clay,” 2009. [Online]. Available: <http://ljs.academicdirect.org/>
- [56] Lesley, “3 Stages of Firing Clay – A Beginners Guide to Firing Pottery Beginner info,” <https://thepotterywheel.com/stages-of-firing-clay/>.
- [57] T. Okada, K., Uchiyama, S., Isobe, Kameshima, Y., Nakajima, N., & Kurata, “Capillary rise properties of porous mullite ceramics prepared by an extrusion method

- using organic fibers as the pore former.,” *Building and Environment*, vol. 55, pp. 110–116, 2009, doi: 10.1016/j.buildenv.2011.12.018.
- [58] Jayawardena D., “The Present Status of the Development of Mineral Resources in Sri Lanka,” 1984.
- [59] M. Nakagawa, K. v Wilbert Kehelpannala B, T. Manabe, L. Ranaweera, and A. Nasu, “Kaolin deposit at meetiyagoda, southwestern sri lanka,” *Clay Science*, vol. 21, pp. 29–34, 2017, doi: 10.11362/jcssjclayscience.21.2_29.
- [60] “Four Methods: The Very Basics Wheel Throwing Hand Building Glazing.” [Online]. Available: <http://www.wikihow.com/Make-Ceramics>
- [61] V. K., “Principles of heat transfer in porous media.,” *Building and Environment*, vol. 57, pp. 362–369, 2015, doi: 10.1016/j.buildenv.2012.06.006.
- [62] Z. H. Zhang R, Feng J, Cheng X, Gong L, Li Y, “Porous thermal insulation materials derived from fly ash using a foaming and slip casting method.,” *Energy and Buildings*, vol. 84, pp. 105–113, 2014, doi: 10.1016/j.buildenv.2014.11.001.
- [63] A. F. Buratti C, Moretti E, Belloni E, “Thermal and acoustic performance evaluation of new basalt fiber insulation panels for buildings.,” *Energy Procedia*, vol. 97, pp. 69–81, 2015, doi: 10.1016/j.buildenv.2015.12.004.
- [64] C. W., “Thermal analysis on the cooling performance of a wet porous evaporative plate for building.,” *energy conservation and management*, vol. 114, pp. 257–266, 2017, doi: 10.1016/j.buildenv.2016.12.028.
- [65] J. Folaranmi, “Effect of Additives on the Thermal Conductivity of Clay”, [Online]. Available: <http://ljs.academicdirect.org>
- [66] S. NA. Kadir A, Zulkifly SNM, Abdullah MMAB, “*The Utilization of Coconut Fibre into Fired Clay Brick*”, *Trans Tech Publications, Switzerland*, vol. 123. Elsevier Ltd, 2016. doi: 10.1016/j.buildenv.2017.07.023.
- [67] S. Maliakal, T and Thiyyakkandi, “Influence of randomly distributed coir fibers on shear strength of clay,” *otechnical and Geological Engineering*, vol. 135, no. December 2017, pp. 194–201, 2013, doi: 10.1016/j.buildenv.2018.03.012.
- [68] C. Puppala, A.J., and Musenda, “Effect of fibre reinforcement on strength and volume change in expansive soils’,” *Transportation Research Record*, vol. 132, no. January, pp. 83–95, 2002, doi: 10.1016/j.buildenv.2018.01.029.

- [69] S. M. K. Y.M. Kim, J.H. Lee, “Effects of double skin envelopes on natural ventilation and heating loads in office buildings,” *Energy and Buildings*, vol. 142, pp. 34–46, 2013, doi: 10.1016/j.buildenv.2018.05.051.
- [70] M.H. Tascon, “Experimental and Computational Evaluation of Thermal Performance and Overheating in Double Skin Facades,” *International Journal of Advances in Engineering & Technology*, vol. 6, no. 4, pp. 1524–1534, 2008.
- [71] W. Jager, “‘Double Skin Facades-sustainable Concepts’, Malmo, Sweden,” *Building and Environment*, vol. 140, no. January, pp. 184–193, doi: 10.1016/j.buildenv.2018.05.033.
- [72] B. M. Wigginton, “Architectural Research Quarterly, Intelligent Glass Facades by Andrea Compagno,” *Bhumi, The Planning Research Journal*, vol. 3, no. 1, p. 25, 2008, doi: 10.4038/bhumi. V 3i1.12.
- [73] Y. García, J. Cuadrado, J. M. Blanco, and E. Roji, “Optimizing the indoor thermal behaviour of housing units in hot humid climates: Analysis and modelling of sustainable constructive alternatives,” *Indoor and Built Environment*, vol. 28, no. 6, pp. 772–789, 2019, doi: 10.1177/1420326X18793965.
- [74] H. Z. Alibaba and M. B. Ozdeniz, “Energy performance and thermal comfort of double-skin and single-skin facades in warm-climate offices,” *Journal of Asian Architecture and Building Engineering*, vol. 15, no. 3, pp. 635–642, 2016, doi: 10.3130/jaabe.15.635.
- [75] W. N. Hien, W. Liping, A. N. Chandra, A. R. Pandey, and W. Xiaolin, “Effects of double-glazed facade on energy consumption, thermal comfort and condensation for a typical office building in Singapore,” *Energy and Buildings*, vol. 37, no. 6, pp. 563–572, 2005, doi: 10.1016/j.enbuild.2004.08.004.
- [76] G. Ballestini, M. De Carli, N. Masiero, and G. Tombola, “Possibilities and limitations of natural ventilation in restored industrial archaeology buildings with a double-skin façade in Mediterranean climates,” *Building and Environment*, vol. 40, no. 7, pp. 983–995, 2005, doi: 10.1016/j.buildenv.2004.09.015.
- [77] W. Ding, Y. Hasemi, and T. Yamada, “Natural ventilation performance of a double-skin façade with a solar chimney,” *Energy and Buildings*, vol. 37, no. 4, pp. 411–418, 2005, doi: 10.1016/j.enbuild.2004.08.002.

- [78] C. Y. Yi and C. Peng, "Microclimate change outdoor and indoor coupled simulation for passive building adaptation design," *Procedia Computer Science*, vol. 32, no. 0, pp. 691–698, 2014, doi: 10.1016/j.procs.2014.05.478.
- [79] Y. Chen, J. Liu, J. Pei, X. Cao, Q. Chen, and Y. Jiang, "Experimental and simulation study on the performance of daylighting in an industrial building and its energy saving potential," *Energy and Buildings*, vol. 73, pp. 184–191, 2014, doi: 10.1016/j.enbuild.2014.01.030.
- [80] E. M. Schau, M. Traverso, A. Lehmannann, and M. Finkbeiner, "Life cycle costing in sustainability assessment-A case study of remanufactured alternators," *Sustainability*, vol. 3, no. 11, pp. 2268–2288, 2011, doi: 10.3390/su3112268.
- [81] J. Schade, "Life cycle cost calculation models for buildings."
- [82] "Life-cycle costing of new processes, materials, and products Executive summary fostering industrial symbiosis for a sustainable resource intensive industry across the extended construction value chain," 2017.
- [83] T. E. Swarr *et al.*, "Environmental life-cycle costing: A code of practice," *International Journal of Life Cycle Assessment*, vol. 16, no. 5, pp. 389–391, Jun. 2011. doi: 10.1007/s11367-011-0287-5.
- [84] R. Emmanuel, "Estimating the environmental suitability of wall materials: Preliminary results from Sri Lanka," *Building and Environment*, vol. 39, no. 10, pp. 1253–1261, Oct. 2004, doi: 10.1016/j.buildenv.2004.02.012.
- [85] C. Udawattha and R. Halwatura, "Life cycle cost of different Walling material used for affordable housing in tropics," *Case Studies in Construction Materials*, vol. 7, pp. 15–29, Dec. 2017, doi: 10.1016/j.cscm.2017.04.005.
- [86] R. Arooz and R. Halwatura, "Prague Decision-Support Tools and Assessment Methods for Sustainable Built Environment Life Cycle Costing And Embodied Energy Analysis Of Self-Compacting In-Situ Cast Mud-Concrete Load Bearing Walling System (MCW)-An Innovative Earth Based Walling Material Application For Energy Efficient Buildings."
- [87] "<https://www.brightubengineering.com/hvac/41262-what-is-psychrometric-chart-components-of-psychrometric-chart/>."

- [88] J. F. Nicol and M. A. Humphreys, “Adaptive thermal comfort and sustainable thermal standards for buildings,” in *Energy and Buildings*, Jul. 2002, vol. 34, no. 6, pp. 563–572. doi: 10.1016/S0378-7788(02)00006-3.
- [89] “<https://humiditycontrol.com/psychrometric-chart/>.”
- [90] M. Kolokotroni and P. Heiselberg, “IEA-EBC Programme-Annex 62 Ventilative Cooling Ventilative Cooling state-of-the-art review.”
- [91] U. Rajapaksha, “Heat stress pattern in conditioned office buildings with shallow plan forms in Metropolitan Colombo,” *Buildings*, vol. 9, no. 2, Jan. 2019, doi: 10.3390/buildings9020035.
- [92] G. Hu, S. Hassanli, K. C. S. Kwok, and K. T. Tse, “Wind-induced responses of a tall building with a double-skin façade system,” *Journal of Wind Engineering and Industrial Aerodynamics*, vol. 168, pp. 91–100, Sep. 2017, doi: 10.1016/j.jweia.2017.05.008.
- [93] “Types of Clay Bodies - Kiln Arts.” <https://kilnarts.org/education/ceramic-pottery/the-basics-of-clay/types-of-clay/> (accessed Jan. 16, 2022).
- [94] Daniel Rhodes, *Clay and Glazes for the Potter*.
- [95] Lesley, “<https://thepotterywheel.com/types-of-clay-for-pottery/#earthenware>”.
- [96] B. Berge, “The Ecology of Building Materials.,” *Building and Environment*, vol. 44, no. 4, pp. 826–838, 2009, doi: 10.1016/j.buildenv.2008.05.020.
- [97] K. A. Heathcote, “Durability of earthwall buildings,” *Construction and Building Materials*, vol. 9, no. 3, pp. 185–189, Jun. 1995, doi: 10.1016/0950-0618(95)00035-E.
- [98] C. W., “Thermal analysis on the cooling performance of a wet porous evaporative plate for building.,” *energy conservation and management*, vol. 114, pp. 257–266, 2017, doi: 10.1016/j.buildenv.2016.12.028.
- [99] “Clay Shrinkage During Drying and Firing | Preventing Defects.” [Online]. Available: [http://www.lakesidepottery.com/HTML Text/Tips/Clay drying and firing process.htm](http://www.lakesidepottery.com/HTML%20Text/Tips/Clay%20drying%20and%20firing%20process.htm)
- [100] N. Phonphuak, M. Teerakun, A. Srisuwan, P. Ruenruangrit, and P. Saraphirom, “The use of sawdust waste on physical properties and thermal conductivity of fired clay brick production,” *International Journal of GEOMATE*, vol. 18, no. 69, pp. 24–29, 2020, doi: 10.21660/2020.69.5706.

- [101] “Goodbye to the cavity wall - Guten Tag! to the fired clay block - Renovate Green.”
- [102] P. M. Nigay, T. Cutard, and A. Nzihou, “The impact of heat treatment on the microstructure of a clay ceramic and its thermal and mechanical properties,” *Ceramics International*, vol. 43, no. 2, pp. 1747–1754, 2017, doi: 10.1016/j.ceramint.2016.10.084.
- [103] L. C. Haw, “Empirical study of a wind-induced natural ventilation tower under hot and humid climatic conditions,” *Energy and Buildings*, vol. 65, no. 2, pp. 153–159, 2012.
- [104] P. M. Nigay, T. Cutard, and A. Nzihou, “The impact of heat treatment on the microstructure of a clay ceramic and its thermal and mechanical properties,” *Ceramics International*, vol. 43, no. 2, pp. 1747–1754, 2017, doi: 10.1016/j.ceramint.2016.10.084.
- [105] ASTM C20-00, “Standard Test Methods for Apparent Porosity, Water Absorption, Apparent Specific Gravity, and Bulk Density of Burned Refractory Brick and Shapes by Boiling Water,” *American Society for Testing and Materials*, vol. 00, no. Reapproved 2015, pp. 1–3, 2015, doi: 10.1520/C0020-00R10.2.
- [106] R. Hyde, *Climate Responsive Design: A Study of Buildings in Moderate and Hot Humid Climates*, vol. 8, no. 15. 2000. doi: 10.5897/SRE12.608.
- [107] N. S. Senanayake, D. Shyamalee, A. D. U. S. Amarasinghe, and N. S. Senanayaka, “Evaluation of different binding materials in forming biomass briquettes with saw dust Power Generation from MSW in Sri Lanka View project Hackathon on Digital Education View Project Evaluation of different binding materials in forming biomass briquettes with saw dust,” *International Journal of Scientific and Research Publications*, vol. 5, no. 3, 2015, [Online]. Available: <https://www.researchgate.net/publication/284534867>
- [108] J. Folaranmi, “Effect of Additives on the Thermal Conductivity of Clay”, [Online]. Available: <http://ljs.academicdirect.org>
- [109] M. Rajapaksha and R. U. Halwatura, “‘Clay’, for tropical interiors.”
- [110] M. Rajapaksha and R. U. Halwatura, “Poro-therm clay wall panel system for indoor cooling,” *2020 From Innovation to Impact, FITI 2020*, 2020, doi: 10.1109/FITI52050.2020.9424896.

- [111] Z. Alwan and P. Jones, "The importance of embodied energy in carbon footprint assessment," *Structural Survey*, vol. 32, no. 1, pp. 49–60, 2014, doi: 10.1108/SS-01-2013-0012.
- [112] R. Arooz and R. Halwatura, "Prague Decision-Support Tools and Assessment Methods for Sustainable Built Environment Life Cycle Costing and Embodied Energy Analysis of Self-Compacting In-Situ Cast Mud-Concrete Load Bearing Walling System (MCW)-An Innovative Earth Based Walling Material Application For Energy Efficient Buildings."