

**FEASIBLE STUDY ON THE POWER QUALITY ISSUES
OF VOLTAGE VARIATION AND HARMONICS DUE
TO PV PENETRATION IN LVDN: A CASE STUDY IN
NEGOMBO LVDN, SRI LANKA**

Sareka Saravanapavan

178634B

Degree of Master of Science

Department of Electrical Engineering

University of Moratuwa

Sri Lanka

February 2024

**FEASIBLE STUDY ON THE POWER QUALITY ISSUES
OF VOLTAGE VARIATION AND HARMONICS DUE
TO PV PENETRATION IN LVDN: A CASE STUDY IN
NEGOMBO LVDN, SRI LANKA**

Sareka Saravanapavan

178634B

Thesis/Dissertation submitted in partial fulfillment of the requirements for the degree
Master of Science in Electrical Installation

Department of Electrical Engineering

University of Moratuwa
Sri Lanka

February 2024

DECLARATION

I, Sareka Saravanapavan declare that this is my own work and this thesis/dissertation does not incorporate without acknowledgement any material previously submitted for a Degree or Diploma in any other University or institute of higher learning and to the best of my knowledge and belief it does not contain any material previously published or written by another person except where the acknowledgement is made in the text.

Also, I hereby grant to University of Moratuwa the non-exclusive right to reproduce and distribute my thesis/dissertation, in whole or in part in print, electronic or other medium. I retain the right to use this content in whole or part in future works (such as articles or books).

Signature:

Date: 03.02.2024

The above candidate has carried out research for the Master of Science in Electrical Installation thesis/Dissertation under my supervision.

Name of the supervisor: Prof. W.D. Asanka S Rodrigo

Signature of the supervisor:

Date: 04/02/2024

Abstract

Renewable energy resources are encouraged all over the world to have a green power generation to avoid global warming due to conventional energy sources. As one of a sustainable power source, solar photovoltaic system is considered in micro grid and domestic solar system. Domestic solar systems have a rapid growth in Sri Lanka since last decade and they are connected with the existing low voltage distribution network. Therefore, it causes power quality issues with increasing PV penetration in LVDN.

The common PQ issue arising from PV penetration is the voltage rise. Therefore, a LVDN with voltage rise issue in Negombo, Sri Lanka was selected for the case study of this research. This research focused on a LVDN with low active power existence and high feeder resistance where the voltage rise is due to feeder resistance with increasing PV penetration. This study considered power quality issues of voltage violation, harmonic analysis and power factor violation in the selected LVDN. Analysis of another LVDN with different transformer capacity was also summarized in this study.

The mitigation techniques of active network management and network reinforcement were applied to the LVDN and the response was analyzed. The harmonic results were insignificant with voltage violation. And when the voltage rise was mitigated with tap settings, the harmonic results were more insignificant compared to the previous. Therefore, harmonic analysis was not carried out for further analysis.

The enhancement of hosting capacity with different mitigation techniques was analyzed while considering voltage violation and power factor violation. The mitigation technique of active network management with balancing loads, tap settings and increasing the loading of the network, increased the hosting capacity from 50kW (31% w.r.t t/f capacity) to 108kW (68%) at no cost. Reactive power compensation schemes did not provide solution as it violates the power factor of the network while mitigating the voltage variation and vice versa. Because, the required reactive power to mitigate the voltage rise becomes significant compared to the active power existence in the network. Mitigation technique of energy storage system also did not provide solution for the low load demand LVDN.

The mitigation techniques of network reinforcement methods were applied. It increased the hosting capacity up to 144kW (90%) with upgrading conductor, 153kW (96%) with the installation of OLTC with AVR and the installation of separate PV feeder did not increase the hosting capacity. The cost estimation was done for the mitigation techniques. And it is concluded that the techno economic feasible solution as upgrading conductor with 95sqmm conductor size is selected as the mitigation technique for this existing system.

The conclusions of this study are as follow. The network reinforcement mitigation techniques are more suitable than the reactive power compensation schemes, for a PV penetrated LVDN with low active power existence and high feeder resistance, in order to increase the PV penetration, when the voltage rise is due to the feeder resistance. Reactive power compensation methods are suitable for the network with high active power existence and/or high reactive power existence, otherwise it would violate the power factor and/or voltage. Installation of solar PV system in the LVDN will make the system better, to overcome from the effect of the high feeder resistance and it will increase the loading capability of the network while maintaining PQ standards. The increase in the day time loading of the network, increases the PV penetration. Mitigation techniques of active network management of balancing loads and tap settings also increases PV penetration at no cost in such LVDN. Feeder resistance and loading of the network give more impact in deciding the hosting capacity of such LVDN. Therefore, the network reinforcement techniques are more suitable for LVDN with low active power existence and high feeder resistance. Future analysis can be extended for a small scale LVDN with PV systems including significant nonlinear loads and reactive loads.

ACKNOWLEDGEMENTS

My sincere gratitude goes to Prof. W.D. Asanka S Rodrigo, Professor in Electrical Engineering, Department of Electrical Engineering, University of Moratuwa, Sri Lanka, for his great insights, perspectives and valuable guidance.

I would like to express my sincere thanks to Prof. W.D.A.S. Wijayapala, Prof. (Ms) Lidula N. Widanagama Arachchige, Dr. (Ms)R.M.T.Damayanthi, Dr.(Mrs) Rasara Samarasinghe and Snr. Prof. Sisil Kumarawadu for their constructive criticism during project progress presentations which helped me to make necessary improvements.

I am thankful to the officers in Post Graduate Office, Faculty of Engineering, University of Moratuwa, Sri Lanka for helping in various ways in my academic works and other relevant things. I also thank the people who serve in the Department of Electrical Engineering Office.

I would like to thank Eng.W.M.A.S Wijeyathunga, Chief Engineer – Negombo Distribution Division, Western Province- North, Ceylon Electricity Board for the extended support given to carry out the thesis work successfully. And my thanks are also extended to the staffs of Negombo Distribution Division for their support.

I would like to thank Deputy General Manager –Research and Development Unit, Ceylon Electricity Board and Deputy General Manager –Western Province - North, Ceylon Electricity Board for the permission given to carry out my research. Also my thanks go to Eng. Asiri Mihindukulasuriya – Engineer in Research and Development Unit to make a success in this project with his continuous support. Lastly, I would like to thank my family for the constant inspiration and guidance which kept me focused and motivated.

TABLE OF CONTENTS

Declaration	i
Abstract	ii
Acknowledgements	iii
Table of Contents	iv
List of Figures	vii
List of Tables	xi
List of abbreviations	xii
1. Introduction	1
1.1 Introduction	1
1.2 Problem Statement	1
1.3 Research Objectives	3
1.4 Research Methodology	3
2. Literature Review	5
3. Analysis of LVDN with PV Penetration – A Case Study in Negombo Distribution Division, CEB, Sri Lanka	11
3.1 Introduction	11
3.2 Data Collection	11
3.3 Assumptions Made for the Analysis	12
3.4 Analysis of Voltage Variation	14
3.5 Mathematical Analysis of Feeder 3	16
4. Mitigation Techniques for LVDN: Active Network Management	17
4.1 Introduction	17
4.2 Balancing Load and PV Generation	21
4.2.1 Methodology	21
4.2.2 Result and Discussion	21
4.2.2.1 Analysis of Voltage Variation	21
4.2.2.2 Harmonic Analysis	22
4.2.2.3 Hosting Capacity with Balanced Load Condition	23
4.3 Tap Settings of Transformer	24

4.3.1	Methodology	24
4.3.2	Result and Discussion	24
4.3.2.1	Analysis of Voltage Variation	24
4.3.2.2	Hosting Capacity with Tap Settings and Balanced Load	25
4.3.2.3	Harmonic Analysis	26
4.4	Demand Side Management	27
4.4.1	Methodology	27
4.4.2	Result and Discussion	28
4.5	Reactive Power Compensation: Reactor Insertion	29
4.5.1	Methodology	29
4.5.2	Result and Discussion	29
4.5.2.1	Reactor Insertion with 15kVAr Reactor	29
4.5.2.2	Reactor Insertion with 40kVAr Reactor	30
4.6	Reactive Power Compensation: Inverter Controller	32
4.6.1	Methodology	32
4.6.2	Volt VAR Controller	32
4.6.2.1	Methodology	32
4.6.2.2	Result and Discussion	34
4.6.3	Watt VAR Controller	39
4.6.3.1	Methodology	39
4.6.3.2	Result and Discussion	39
4.7	Installation of Energy Storage System	40
4.7.1	Methodology	40
4.7.2	Result and Discussion	40
5.	Mitigation Techniques for LVDN: Network Reinforcement	43
5.1	Introduction	43
5.2	Upgrading Conductors	43
5.2.1	Methodology	43
5.2.2	Result and Discussion	44
5.2.2.1	Choice 1: ABC 3 x 95sqmm + N 70sqmm	45

5.2.2.2 Choice 2: ABC 3 x 120sqmm + N 70sqmm	48
5.3 Separate Feeder for Solar PV Customers	50
5.3.1 Methodology	50
5.3.2 Result and Discussion	50
5.4 Installation of On Load Tap Changer (OLTC) with AVR	51
5.4.1 Methodology	51
5.4.2 Result and Discussion	51
5.4.2.1 Mathematical Analysis	51
5.4.2.2 Hosting Capacity	51
6. Budget Estimation of Mitigation Methods	53
6.1 Estimated Budget for Upgrading Conductors	53
6.2 Estimated Budget for On Load Tap Changer with AVR	54
6.3 Estimated Budget for Energy Storage System	55
6.4 Comparison of Estimated Budget	55
6.5 Comparison of Unit Cost for Mitigation Techniques	56
7. Analysis of 250kVA Transformer	57
7.1 Mathematical Analysis for Selection of Conductor Size	57
7.2 Hosting Capacity	58
7.2.1 Methodology	58
7.2.2 ABC Conductor of 120sqmm	58
7.2.2.1 Result and Discussion	58
7.2.3 ABC Conductor of 150sqmm	59
7.2.3.1 Result and Discussion	59
7.3 Mitigation Techniques of Inverter Controller – VVC	60
7.3.1 Methodology	60
7.3.2 Result and Discussion	61
7.4 Installation of On Load Tap Changer (OLTC) with AVR	63
7.4.1 Methodology	63
7.4.2 Result and Discussion	63

LIST OF FIGURES

Figure 2.1	Saudi Distribution Network and Voltage variation at selected node for different loading condition	5
Figure 2.2	Voltage variation After using active power controller and After using reactive power controller	5
Figure 2.3	Voltage variation with coordination of reactive power injection & active power curtailment and Power flow chart	6
Figure 2.4	Specifications of distribution feeders	6
Figure 2.5	Variation of V_r VS P_r and Voltage rise & voltage reduction range on the P-V curve	7
Figure 3.1	IEEE standard Residential load profile and Commercial load profile	13
Figure 3.2	Design of feeder 1 & 2 and feeder 3	14
Figure 3.3	Voltage profile along the feeder with PV capacity of 44kW and 64kW(before & after adding the 20kW customer	15
Figure 3.4	Daily voltage profile at the feeder end with PV capacity of 64kW	15
Figure 4.1	Volt-Watt curve	20
Figure 4.2	Watt- VAR Curve	20
Figure 4.3	Voltage profile along the feeder at a loading of 20kW(minimum) and 86kW(maximum)	21
Figure 4.4	Daily voltage profile at the feeder end and Power flow result	22
Figure 4.5	Variation of Harmonic Voltage with Harmonic order	22
Figure 4.6	Voltage profile along the feeder at hosting capacity of 50kW and Daily voltage profile at the feeder end	23
Figure 4.7	Voltage profile with regulator $V_{reg}=230$ At the max loading of 85.9kW and min loading of 20kW	24

Figure 4.8	Night time voltage profile and Change in regulator tap position at $V_{reg}=230$	24
Figure 4.9	Voltage profile along the feeder at HC of 80kW & 20kW loading and Daily voltage profile at the feeder end at HC of 80kW	26
Figure 4.10	Variation of Harmonic Voltage with Harmonic order	26
Figure 4.11	Voltage profile at a loading of 95.7kW at the absence of PV generation and at Hosting capacity of 108kW	28
Figure 4.12	Daily voltage profile at 114kW PV capacity & 85.9kW max loading with daily load profile	29
Figure 4.13	Daily voltage profile at the feeder end with 15kVAR reactor at PV capacity of 114kW	29
Figure 4.14	Daily voltage profile with 15kVAR reactor at PV capacity of 96kW(60%) and power flow result	30
Figure 4.15	Daily voltage profile with 40kVAR reactor at PV capacity of 114kW and Power flow result	31
Figure 4.16	Volt VAR Curve	32
Figure 4.17	Daily voltage profile at feeder end and Daily Volt – VAR curve	34
Figure 4.18	Daily reactive power variation and Power flow result with Volt – VAR Controller	34
Figure 4.19	Daily power factor variation and Active & Reactive power variation with Volt VAR controller	35
Figure 4.20	Daily Power factor variation and Daily reactive power variation at the transformer end	36
Figure 4.21	Daily Power factor variation at the transformer end at different loading conditions	37
Figure 4.22	Daily active and reactive power variation at the transformer end at different loading conditions	37
Figure 4.23	Daily voltage profile at the feeder end with Watt – VAR controller	39

Figure 4.24	Daily active and reactive power variation at the controlled inverter	39
Figure 4.25	Daily active power variation of the storage element and The transformer with ESS of 50kWh capacity	40
Figure 4.26	Daily voltage Profile	40
Figure 4.27	Daily active power variation of the storage element and The transformer with ESS of 1MWh capacity	41
Figure 4.28	Daily active power variation of the storage element and The transformer with ESS of 2MWh capacity and the daily energy variation of ESS	41
Figure 5.1	Voltage profile along the feeder with ABC 3 x 95sqmm + N 70sqmm, ABC 3 x 120sqmm + N 70sqmm & ABC 3 x 150sqmm + N 70sqmm respectively	45
Figure 5.2	Voltage profile during night time and day time at Hosting Capacity of 126kW and max loading of 85.9kW	46
Figure 5.3	Day time voltage profile at HC of 100kW and min loading of 20kW	46
Figure 5.4	Voltage profile during night and day time at HC of 144kW(90%) and possible max loading of 110kW	47
Figure 5.5	Daily variation of reactive power	47
Figure 5.6	Voltage profile during night time and day time at HC of 160kW and possible max loading of 130kW	48
Figure 5.7	Day time voltage profile at HC of 160kW and loading of 86kW	49
Figure 5.8	Voltage profile during night time and day time at HC of 160kW and loading of 75kW	49
Figure 5.9	Voltage profile along the feeder at HC of 76kW and loading of 85.9kW	50
Figure 5.10	Voltage profile along the feeder at max loading 138kW (86.25%) without PV_and with PV Capacity of 153kW(96%)	52

Figure 7.1	Voltage profile along the feeder at a loading of 140kW and HC of 176kW during night time and day time respectively	58
Figure 7.2	Voltage profile along the feeder at a loading of 165kW and HC of 197kW during night time and day time respectively	59
Figure 7.3	Daily voltage profile and daily Volt – VAR curve	61
Figure 7.4	Daily variation of active and reactive power with different loading conditions	61
Figure 7.5	Daily variation of power factor with different loading conditions	62
Figure 7.6	Voltage profile along the feeder at max loading of 220kW (88%) and HC of 220kW during night and day time respectively	63

LIST OF TABLES

Table 5.1	Voltage rise at the feeder end with conductor size	44
Table 6.1	Budget estimation for upgrading conductor of 95sqmm	53
Table 6.2	Budget estimation for upgrading conductor of 120sqmm	53
Table 6.3	Budget estimation for upgrading conductor of 150sqmm	54
Table 6.4	Budget estimation for On Load Tap Changer with AVR	54
Table 6.5	Budget estimation for Energy Storage System	55
Table 6.6	Comparison of Estimated Budget	55
Table 6.7	Comparison of unit cost for mitigation techniques	56
Table 7.1	Comparison of results with different conductor sizes	60

LIST OF ABBREVIATIONS

Abbreviation	Description
DN	Distribution network
DG	Distribution generators
ESS	Energy storage system
HC	Hosting capacity
LV	Low Voltage
LVDN	Low voltage distribution network
Max	Maximum
Min	Minimum
MV	Medium voltage
MVDN	Medium voltage distribution network
PQ	Power quality
t/f	Transformer
VVC	Volt VAR Control
w.r.t	with respect to