

**SEQUENCING BATCH REACTOR TREATMENT OF
GARMENT FACTORY EFFLUENTS IN SRI LANKA:
AN EMPIRICAL VALUE FOR AERATION FACTOR**

W.M.C WijayAthunga

This dissertation was submitted in requirements for the Master of Engineering degree in Water Resources Engineering and Management.

Department of Civil Engineering,

University of Moratuwa.

Sri Lanka

September 2008

93929

Abstract

Most factories located outside the DOI industrial zones in Sri Lanka do not have proper sewage treatment systems and due to the high number of employees these factories are always encountered with the problem of handling large quantities of low strength sewage generated from lavatories, canteens and kitchens. In such factories sewage is usually handled using conventional septic tank - soakage pit systems. Such systems are commonly found infested with insects, and promote further breeding. They cause nuisance due to obnoxious odor, and is a major cause for severe ground and surface water pollution. It has been noted that these factories have critical problems of handling sewage during rainy season, especially when the factor) is located in areas with high ground water table such as a marshy land or near a surface water body.

To solve the problem of handling septic tank effluents. Sequencing Batch Reactor (SBR) treatment plants have been provided in several factories due to their lower cost and minimum use of land area. Most of these plants produce effluents of quality far better than what is stipulated by the Central Environmental Authority (CEA) effluent standards. Parameters such as BOD are sometimes being reduced even down to undetectable levels which are rather unnecessary. Moreover, it has been noted by the industry that there may be possibilities to cut down the monthly electrical cost by operating the treatment plants at optimal levels of treatment. On the other hand, treatment plant contractors have noted that the bid prices were relatively high due to over-treatment specified and set under conventional design criteria.

Over-treatment and possibly higher than necessary, raw-BOD value for design purposes, seem to be the problem areas. Therefore, it is important to find a better value for aeration factor expressed in terms of oxygen dissolved in clean water (ODCW), for the use in calculations of aerobic sewage treatment plant designs, treating septic tank effluents. The lengthy calculations needed for designing aeration tanks and selection of number and type of aerators are therefore perceived to be correctly, easily and quickly done if a proper empirical value for aeration factor is available. This research was therefore carried out with the following objectives:

1. A reasonably accurate value for the oxygen requirement in oxidation of 1 kg of BOD

(Aeration factor) used in design calculations.

2. To propose a reasonably correct value for septic tank effluent BOD for garment factories.

3.To calculate the cost saving with a new value of aeration factor both operational and capital.

It was found by the experiments carried out in this research, and samples taken simultaneously elsewhere that the average septic tank effluent BOD was around 250 mg/1 and ranged between 186 mg/1 to 284mg/1 against the previously used value of 300 mg/1 which is 17% less.

The aeration factor used for carbonaceous oxygen in designing above SBR plants was 4kgO_i/kg BOD and the value proposed in literature for various other countries range from 1- 2.5 kgO₂/kg BOD depending on temperature fluctuations. This research suggests 3.5 kgO₂/kg BOD, as an appropriate value for respiration factor in treating septic tank effluents from Sri Lankan garment factories. This is a reduction of 12.5% in oxygen requirement compared to previously used value.

The effect of application of above two parameters in the form of electrical power and capital saving were approximately 27% and 25% respectively for the particular SBR design used for them research.

DECLARATION

I hereby declare that the work included in this dissertation, in part or whole has not been submitted for any other academic qualification at any institution.

Eng. W.M.C. Wijayatunga

Certified by:

Dr. Jagath Manatunge
Project Supervisor
Department of Civil Engineering
University of Moratuwa
Sri Lanka



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

ACKNOWLEDGEMENTS

The author gratefully acknowledges the tremendous help and support given throughout the course of the research leading to the completion of this study by a number of individuals and institutions in making this study possible.

I would, first, like to express my sincere and most profound gratitude to Dr. Jagath Manatunge, my advisor, for reading, studying and accepting the research proposal and then for allocating his valuable time, suggestions, comments, getting down articles on related topics from various websites and deep understanding and kindness despite his busy schedule.

My wholehearted gratitude is extended to Prof. Mrs. Niranjanie Ratnayake for accepting my research proposal, for her advice and suggestions on improving the research and also arranging Dr. Manatunge to supervise the project. Thanks are also due to Dr. Mahesh Jayaweera for his invaluable input during progress reviews.

The staff of the Environmental engineering laboratory Mrs. Nilanthi Gunathilake, Mr. Justin Silva, Mrs. Manjula Ranasinghe and the research students are remembered with admiration for all their support extended to me.

Sincere thanks also extended to Head of Department and University authorities for providing me with excellent facilities at the university during the Postgraduate programme. All of my batch mates are remembered with pleasure for their kind cooperation extended during the period of study and persuading me to complete the research project.

W.M.C. Wijayatunga



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

TABLE OF CONTENTS

Description	Page
Declaration	01
Acknowledgements	02
Abstract	03
Table of Contents	04
List of Tables	06
List of Figures	07
List of Abbreviations	08
Chapter 1	
1.0 INTRODUCTION	09
1.1 Domestic wastewater treatment	
1.1.1 Treatment of domestic wastewater in SBR system	
1.1.2 Present scenario in the Sri Lankan garment industry	
1.1.3 Problem identification: a case study	
Chapter 2	
2.0 THEORITICAL CONSIDERATIONS AND LITERATURE REVIEW	15
2.1 Strength of septic tank effluent	
2.1.1 Changing the value of aeration factor	
2.1.2 Nitrogen removal	
2.1.3 Phosphorus removal	
2.1.4 Variation of oxygen required	
2.2 Oxygen transfer in wastewater	
2.2.1 Oxygen requirement for septic tank effluent	
2.3 Objectives of the study	
Chapter 3	
3.0 MATERIALS AND METHOD	22
3.1 Study area	
3.1.1 Methodology	
3.2 Present method of operation	
3.3 Sampling for research	
3.3.1 Specimen calculation	

Chapter 4		
4.0 RESULTS AND DISCUSSION		27
4.1	Results	
4.2	Discussion	
4.2.1	Septic tank effluent BOD	
4.2.2	Aeration factor	
4.2.3	Saving in running electrical cost	
4.2.4	Saving in construction cost	
Chapter 5		
5.0 CONCLUSION AND RECOMMENDATIONS		37
5.1	Conclusions	
5.2	Recommendations	
5.3	Further studies recommended	
Chapter 6		
6.0 REFERENCES		39
Chapter 7		
7.0 APPENDICES		41
Chapter 8		
8.0 ANNEXURES		51



University of Moratuwa, Sri Lanka.
 Electronic Theses & Dissertations
www.lib.mrt.ac.lk

LIST OF TABLES

Table 1: No. of sewage treatment plants constructed during 2004 - 2007

Table 2: Over treatment of septic tank effluent in various plants

Table 3: Aeration factors and aeration times

Table 4: Aeration factors and aeration times with effluent quality

Table 5: Aeration factors and aeration times - summary

Table 6: Aeration factors and aeration times for $T = 2.826d$

Table 7: Aeration factor and respiration factor

Table 8: Aeration factors and aeration times for J.K. Garments

Table 9: Aeration factor and respiration factor for J.K. Garments

Table 10: T – Theoretical vs. T – Practical for J.K. Garments



University of Moratuwa, Sri Lanka.
Electronic Theses & Dissertations
www.lib.mrt.ac.lk

LIST OF FIGURS

Figure 1: Suspended and attached growth systems

Figure 2: Suspended growth system

Figure 3: Attached growth system

Figure 4: Activated sludge process

Figure 5: SBR Process sequence

Figure 6: Septic tank effluent collection system

Figure 7: Position of the SBR with respect to surrounding structures

Figure 8: Internal dimensions and water level of SBR

Figure 9: Photograph of the SBR

Figure 10: Operating SBR plant

Figure 11: Inside photograph of an SBR

Figure 12: Effluent BOD vs. Aeration time

Figure 13: Aeration time vs. Aeration factor

Figure 14: Effluent BOD vs. Aeration time – J.K. Garments

Figure 15: Aeration time vs. Aeration factor – J.K. Garments

Figure 16: T - Theoretical vs. T – Practical for J.K. Garments

LIST OF ABBREVIATIONS

BOD – Bio-chemical Oxygen Demand

BOI – Board of Investments

BPR – Biological Phosphorus Removal

CEA – Central Environmental Authority

COD – Chemical Oxygen Demand

COR – Carbonaceous Oxygen Requirement

DO – Dissolved Oxygen

GL – Ground Level

MCRT – Mean Cell Residence Time

MLSS – Mixed Liquor Suspended Solids

ODCW – Oxygen Dissolved in Clean Water

PHB – Poly-Hydroxy-Butyrate

SBR – Sequencing Batch Reactor

SOTR – Standardized Oxygen Transfer Rate

SRT – Solids Retention Time

SS – Suspended Solids

STP – Sewage Treatment Plant

TKN – Total Kjeldahl Nitrogen

VSS – Volatile Suspended Solids

WL – Water Level

WWTP – Wastewater Treatment Plant

